ECX FLAT 32 L ∅32 mm, brushless, with integrated electronics

High Torque, 4-Q-Speed Controller

Key data: 80 W, 73.9 mNm, 14 000 rpm



M 1:1

	Drive data		
1_	Nominal power supply voltage	V	24
2_	Nominal speed	rpm	10 000
3_	Nominal torque at 25 °C	mNm	73.9
5_	Nominal supply current at 25 °C	A	4.9
7_	Maximum speed at nominal voltage	rpm	13 318
8_	Maximum permissible drive speed	rpm	14 000
9_	Maximum torque (short-time)	mNm	119
10_	Maximum supply current (short-time)	A	7.2
11_	Rotor inertia of the drive	gcm²	30.7
12_	Nominal supply voltage + V_{CC}	V	8...28
13_	Mechanical time constant	ms	3.69
	Speed constant	rpm/V	592
37_	Speed set value input	V	0...10
38_	Scale speed set value input	rpm/V	1000
	Min. permissible drive speed	rpm	200
40_	Max. acceleration	rpm/s	20 000

	Thermal data		
14_	Thermal resistance housing-ambient	K/W	3.01
15_	Thermal resistance winding-housing	K/W	3.73
16_	Thermal time constant winding	s	12.3
17_	Thermal time constant drive	s	107
18_	Ambient temperature	°C	-25...+85

	Mechanical data		
19_	Axial play at axial load	< 4 N	0 mm
		> 4 N	0.14 mm
	Direction of force		Pull
20_	Radial play		preloaded
21_	Max. axial load (dynamic)	N	4
22_	Max. force for press fits (static)	N	45
	(shaft supported)	N	1000
23_	Max. radial load [mm from flange]	N	12 [5]

	Other specifications		
24_	Weight of the drive	g	71.2

Drive data in the table is nominal data.

Protective functions
Overload protection, blockage protection, inverse-polarity protection, thermal overload protection, low/high voltage cut-off

Connection, Supply (Cable AWG 20)

red	Pin 1 +V_{CC} 8...28 VDC
black	Pin 2 GND
Connector	**Article number**
Molex	39-01-2020

Connection, I/O's (Cable AWG 28)

white	Pin 1 I/O 1
green	Pin 2 I/O 2
grey	Pin 3 I/O 3
brown	Pin 4 I/O 4
Connector	**Article number**
Molex	43025-0400

Operating range



Continuous operation
Continuous operation with reduced thermal resistance R_{th2} 50%
Short term operation

Modular system Details on catalog page 44

Gear	Stages [opt.]	Sensor	Motor Control
399_GPX 32 A/C	1–3	integrated	integrated
400_GPX 32 LN/LZ	1–3		
401_GPX 32 HP	2–4		
402_GPX 32 UP	1–4		
403_GPX 37 A	3		
404_GPX 37 LN/LZ	3		

Configuration

Shaft, front: Length/shaft shoulder/faces
Shaft, rear: Length/shaft shoulder
Motor controller: I/O functionality/system parameters

© 2025 maxon. All rights reserved. February edition. Provisional data. Subject to change.